

Part No.: 760184

18-4 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications of a plenum rated four conductor unshielded cable used for fire protective signaling circuit applications.

Construction Details

Number of Conductors: 4/C
Conductor: 18AWG Solid Bare Copper
Insulation Material: Remguard Plenum Polymer
Nominal Insulation Thickness: 0.010 in.
Nominal Insulation Diameter: 0.060 in.
Color Code: Red, Black, Green, White
Jacket Material: Remguard Plenum Polymer
Jacket Color: Red or Per Customer Requirement
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.175 in.
Surface Print: 3122598 FPLP 18AWG (ETL)US +
Sequential Footage Marking

Electricals

Suggested Working Voltage: 300 Volts, rms.



Technical Details

Temperature Rating
Operation: -2°C to +60°C
Nominal Weight: 30 lbs. / 1,000 Feet

Standards

NEC Article 760
UL Subject 1424, Type FPLP

Codes & Listings

(ETL)US

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.