

Part No.: R00404

22-4 Unshielded Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications for a riser rated four conductor cable used for fire protective signaling circuit applications.

Construction Details

Number of Conductors: 4/C
Conductor: 22AWG Solid Bare Copper
Insulation Material: Polyvinyl Chloride
Nominal Insulation Thickness: 0.010 in.
Nominal Insulation Diameter: 0.045 in.
Color Code: Black, Red, White, Green
Jacket Material: Polyvinyl Chloride
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.140 in.
Surface Print: 3122598 FPLR 22AWG (ETL)US +
Sequential Footage Marking

Electricals

Suggested Working Voltage: 300 Volts, rms.



Technical Details

Temperature Rating
Operation: -20°C to +60°C
Nominal Weight: 15 lbs. / 1,000 feet

Standards

NEC Article 760
UL Subject 1424, Type FPLR

Codes & Listings

(ETL)US

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.