

Part No.: 725103

RG6 Coaxial Cable Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications for a RG 6/U Quad Shield Type 75 ohm plenum coaxial cable used for video display, point-of-sale terminals, local area network, controls and CATV broadcast applications.

Construction Details

Center Conductor: 18AWG Solid Bare Copperweld
Dielectric Material: Foamed FEP
Nominal Dielectric Core O.D: 0.176 in.
1st Shield: Aluminum/Polyester Tape. (100% coverage)
2nd Shield: Aluminum Braid.
3rd Shield: Aluminum/Polyester Tape (100% coverage)
4th Shield: Aluminum Braid
Jacket Material: Remguard Plenum Polymer
Nominal Overall Diameter: 0.275 in.
Jacket Color: Per Customer Requirement
Surface Print: 3122598 CMP 18AWG RG-6/U
QUAD SHIELD OR CATVP C(ETL)US FT6
Sequential Footage Marking

Electricals

Nominal Capacitance: 17.3 pF/ft
Nominal Characteristic Impedance: 75 ohm
Nominal Velocity of Propagation: 78%
Nominal Attenuation dB per 100 feet::
0.66 dB @ 50 MHz
2.10 dB @ 100 MHz
3.00 dB @ 200 MHz
4.50 dB @ 400 MHz
6.40 dB @ 700 MHz
7.90 dB @ 900 MHz



Technical Details

Temperature Rating
Operation: -2°C to 60°C
Nominal Weight: 37 lbs. / 1,000 ft.

Standards

NEC Article 800
Types CMP CATVP

Codes & Listings

C(ETL)US CMP

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.