

Part No.: 725163

16-4 Shielded Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications for a plenum rated four conductor shielded cable used for remote control and signaling power limited circuit applications.

Construction Details

Number of Conductors: 4/C
Conductor: 16AWG Stranded bare copper
Insulation Material: Remguard Plenum Polymer
Nominal Insulation Thickness: 0.007 in.
Nominal Insulation Diameter: 0.072 in.
Color Code: Black, Natural, Red, Green
Shield: Aluminum/Polyester Tape (100% Coverage)
Drain: Stranded Tinned Copper
Jacket Material: Remguard Plenum Polymer
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.207 in.
Surface Print: 3122598 CMP 16AWG C(ETL)US
FT6 + Sequential Footage Marking

Electricals

Suggested Working Voltage: 300 Volts, rms.



Technical Details

Temperature Rating
Operation: -2°C to +60°C
Nominal Weight: 48 lbs. / 1,000 ft.

Standards

NEC Article 800
CMP Rating FT6

Codes & Listings

C(ETL)US

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.