

Part No.: 900903

16-3 Shielded Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications of a three conductor shielded cable used for communication applications.

Construction Details

Number of Conductors: 3/C
Conductor: 16AWG Stranded Bare Copper
Insulation Material: Polyvinyl Chloride
Nominal Insulation Thickness: 0.008 in.
Nominal Insulation Diameter: 0.074 in.
Color Code: Black, White, Red
Shield: Aluminum/Polyester Tape (100% Coverage)
Drain: Stranded Tin Copper
Jacket material: Polyvinyl Chloride
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.195 in.

Electricals

Suggested Working Voltage: 300 Volts, rms.



Technical Details

Temperature Rating
Operation: -20°C to +60°C
Nominal Weight: 38 lbs. / 1,000 feet

Standards

NEC Article 800
UL Subject 444
CMR Rating FT4

Codes & Listings

UL Subject 444, Type CMP

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.