

Part No.: 6DB234STP

Category 6 Shielded 250MHz Polyethylene Jacket

Made in the USA

Applications

Supports all category 6 applications including Ethernet 100BASE-TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth applications such as 622 ATM, Wideband, Ethernet 1000BASE-T and emerging applications with anticipated data rates to 3.2 Gbps.

Construction Details

No. 23 AWG solid bare copper conductor insulated with polyolefin. Two colored mated insulated conductors twisted together to form a pair and four pairs assembled around a pair separator to form a core. The core is overall shielded and jacketed with polyethylene.

Suitable for outdoor use.

Surface Print: 4 PAIR STP 234 AWG SOLID CAT6 SUITABLE FOR OUTDOOR USE DIRECT BURIAL

+ Sequential Footage Marking

Electricals

Mutual Capacitance: 14 pF/ft nominal

Capacitance Unbalance: 330 pF/ft maximum


Velocity of Propagation: 70%

Max. Conductor D.C.R.: 28.6 ohm/1000 feet

Max. DCR Unbalance: 5%

Max. Delay Skew: 45.0ns/100m

Characteristic Impedance: from 0.772 ohm 100 MHz 100 ohm 15%
from 101 ohm 250 MHz 100 ohm 22%



Technical Details

Temperature Rating

Installation -0°C to 50°C

Operation -20°C to 60°C

Nominal Diameter 0.305 in.

Nominal cable weight: 49 lb/1000 feet

Standards

ANSI/TIA/EIA 568C.2 Category 6

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.

Color Code:

Pair	Color Code
1	Blue with White
2	Orange with White
3	Green with White
4	Brown with White