

Part No.: 6UA234UTP

Category 6A Augmented 500 MHz Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Applications

Supports all category 6A applications including Ethernet 10 Gigabit, 100BASETX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422.

Construction Details


No. 23 AWG copper conductor insulated with polyethylene.
Two colored mated insulated conductors twisted together to form a pair and four pairs assembled around a pair separator to form a core.
The core is jacketed with a flame retardant PVC.

Electricals

Mutual Capacitance: 14 pF/ft nominal
Capacitance Unbalance: 330 pF/ft maximum
Velocity of Propagation: 70%
Max. Conductor D.C.R.: 28.6 ohm/1000 feet
Max. DCR Unbalance: 5%
Max. Delay Skew: 45 ns/100m
Characteristic Impedance: from 0.772 - 100 MHz $100 \pm 15\%$
from 101 - 200 MHz $100 \pm 22\%$
from 201 - 500 MHz $100 \pm 32\%$

Color Code:

Pair	Color Code
1	Blue with White
2	Orange with White
3	Green with White
4	Brown with White



Technical Details

Temperature Rating
Installation: -0°C to 50°C
Nominal Diameter: 0.320 in.
Operation: -20°C to 60°C
Maximum Installing Tension: 40.8 lbf
Minimum Bending Radius: 1.250 inch
Nominal Cable Weight: 44 lb/1000 feet

Standards

ANSI/TIA/EIA 568C.2 Category 6A
National Electric Code - Article 800
11801:2002 Category 6A

Codes & Listings

CMR Rating FT4
C(ETL)US CMR

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available.
Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.

Electrical Characteristics:

Frequency MHz	Return Loss	Insertion Loss	NEXT	PS-NEXT	ACRF	PS-ACRF	Prop. Delay	Alien Crosstalk	
	(dB/100m) Minimum	(dB/100m) Maximum	(dB/100m) Minimum	(dB/100m) Minimum	(dB/100m) Minimum	(dB/100m) Minimum	(dB/100m) Maximum	PS ANEXT (dB/100m) Minimum	PS AACRF (dB/100m) Minimum
1	20.0	2.0	74.3	72.3	67.8	64.8	570.0	67.0	67.0
4	23.0	3.8	65.3	63.3	52.8	52.8	552.0	67.0	66.2
8	24.5	5.3	60.8	58.8	46.7	46.7	546.7	67.0	60.1
10	25.0	5.9	59.3	57.3	44.8	44.8	545.4	67.0	58.2
16	25.0	7.4	56.2	54.2	40.7	40.7	543.0	67.0	54.1
20	25.0	8.3	54.8	52.8	38.8	38.8	542.0	67.0	52.2
25	24.3	9.3	53.3	51.3	36.8	36.8	541.2	67.0	50.2
31.25	23.6	10.5	51.9	49.9	34.9	34.9	540.4	67.0	48.3
62.5	21.5	14.9	57.4	45.4	28.9	28.9	538.6	65.6	42.3
100	20.1	19.1	44.3	42.3	24.8	24.8	537.6	62.5	38.2
155	18.8	24.0	41.4	39.4	21.0	21.0	536.9	59.6	34.4
200	18.0	27.5	39.8	37.8	18.8	18.8	536.5	58.0	32.2
250	17.3	31.0	38.3	36.3	16.8	16.8	536.3	56.5	30.2
300	16.8	34.2	37.1	35.1	15.3	15.3	536.1	55.3	28.7
350	16.3	37.2	36.1	34.1	13.9	13.9	535.9	54.3	27.3
400	15.9	40.0	35.3	33.3	12.8	12.8	535.8	53.5	26.2
500	15.2	45.2	33.8	31.8	10.8	10.8	535.6	52.0	24.2