Part No.: 725188

18-8 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Applications

This document establishes the specifications for a plenum rated eight conductor unshielded cable low voltage communication applications.

Construction Details (Overall)

Number of Conductors: 8/C
Conductor: 18AWG Stranded Bare Copper
Stranding: 7 Strands
Insulation Material: Remguard Plenum Polymer
Nominal Insulation Thickness: 0.007 in.
Nominal Insulation Diameter: 0.060 in.
Color Code: Black, Natural, Red, Green, Blue, Brown, Orange, Yellow
Shield: N/A
Drain: N/A
Jacket Material: Remguard Plenum Polymer
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.220 in.
Rip Cord: Nylon
Jacket Color: Per Customer Requirement
Surface Print: 3122598 CMP/FPLP 18AWG C(ETL)US FT6 MADE IN USA
Sequential Footage Marking

Electricals

Suggested Working Voltage: 300 Volts, rms.

Technical Details

Temperature Rating
Operation: -2°C to 60°C
Nominal Weight: 36 lbs. / 1,000 ft.

Standards

NEC Article 800, 760
CMP/FPLP Type FT6

Codes & Listings

C(ETL)US CMP

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.

Remee Products Inc.
P.O. Box 488 1751 Highway Rt.17A
Florida, New York 10921
t: 800.431.3864 e:info@remee.com
© 2014 Remee Products All Right Reserved