

Part No.: CH1002F

16-2 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Applications


This document establishes the specifications for a two conductor cable used in communication applications

Construction Details

Number of Conductors: 2/C
Conductor: 16 AWG 65/34 Bare Copper
Insulation Material: Polyvinyl Chloride
Nominal Insulation Thickness: 0.012 in.
Nominal Insulation Diameter: 0.080 in.
Color Code: Black, Red
Jacket Material: Polyvinyl Chloride
Nominal Jacket Thickness: 0.018 in.
Nominal Diameter: 0.204 in
Surface Print: 3122598 HI-STRAND AUDIO
CABLE 2 COND 16AWG 65
STRAND CMR/CL3R 75°C
C(ETL)US FT4 MADE IN USA"
SUITABLE FOR OUTDOOR USE"
OXYGEN FREE COPPER
+ Sequential Footage Marking

Electricals

Suggested Working Voltage: 300 Volts, rms.



Technical Details

Temperature Rating
Operation -20°C to +75°C
Nominal Weight: 31 lbs. / 1,000 Feet

Standards

NEC Article 800
UL Subject 444, Type CMR/CL3R FT4

Codes & Listings

C(ETL)US Type CMR/CL3R FT4

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Warranty Info

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.