


Part No.: 11-XXX-76E-AYNONF

11 Series Distribution Tight Buffer SM Enhanced (2-12 Fiber) OFNR

Scope

This document establishes the specification requirements for a singlemode OS2 distribution fiberoptic cable. This cable construction consists of singlemode fibers in a distribution tight-buffered design with a riser rated PVC jacket suitable for indoors.



Applications

Riser Indoor

Applicable Documents

- TIA/EIA FOTP Standards 455
- Color Coding of Fiber Optic Cables TIA/EIA-598
- UL 1666
- GR-409-CORE

Overall Cable Construction

- Tight Buffered Fiber
- Dimension: 900 μ m, nominal.
Tight buffered fiber color code: 1-blue, 2-orange, 3-green, 4-brown, 5-slate, 6-white, 7-red, 8-black, 9-yellow, 10-violet, 11-rose, and 12-aqua.
- Cable strength
Aramid yarns are pulled in with the tight-buffered fibers under the outer jacket.
- Outer Sheath
Yellow riser rated PVC jacket (or color per customer request)
- Cable Markings
REMFO 11 SERIES, FIBER OPTIC CABLE, XX (No. of fibers)-SM, REMEE PRODUCTS CORP., MM/YY (month & year of manufacture), OFNR C(ETL)US, Sequentially meter marked.
- Special print as required by customer

Fiber Attenuation

$\leq 0.40/0.30$ dB/km

Mechanical & Environmental Performance

