


Part No.: 22-XXX-74E-EBSXWN

## 22 Series Loose Tube Single Jacket SM Enhanced

### Scope

This document establishes the specifications for an outdoor, all dielectric, low water peak singlemode, dry block fiber optic cable in a loose buffer tube design.



### Applications

Outdoor duct/aerial lashed

### Applicable Documents

TIA/EIA FOTP Standards 455

- Color Coding of Fiber Optic Cables TIA/EIA-598
- RUS 1755.900
- GR-20-CORE

### Overall Cable Construction

- Buffer tube
- High Modulus Polymeric material.  
Dimension: 2.8 mm, nominal for 76 fibers, 2.2mm, nominal for a 4 fiber cable and 1.98mm, nominal for a 2 fiber cable.
- Tube and fiber color code per EIA/TIA-598 or as specified by customer.
- Filling compound: A non-toxic and dermatological safe antioxidant hydrocarbon based gel.
- Dielectric Central strength member.  
Epoxy glass rod with an up-coat of polymer (if necessary per construction).
- Water swellable yarns are to be pulled in with the CSM.
- Cable Core:  
The cable elements are stranded around the CSM, using reverse oscillation.  
Moisture Resistance: A water blocking tape is applied over the cable core to prevent water ingress and migration with a nominal of 25% overlap.
- Non-wicking binder yarns are applied over the core tape.
- Cable strength  
Circumferential strength members are placed over the cable core and under the outer sheath.
- Outer Sheath  
UV Resistant Black Polyethylene. (or color per customer request)  
A ripcord is applied under the outer sheath.
- Cable Markings  
REMFO 22 SERIES, FIBER OPTIC CABLE, # of fibers-SM, REMEE PRODUCTS CORP., TELEPHONE HANDSET SYMBOL, MM/YY (Month & Year of manufacture), Sequentially meter marked. Special print as required by customer.

## Fiber Attenuation

$\leq 0.35/0.25$  dB/km

## Mechanical & Environmental Performance

Maximum Tensile Load for:  
- Installation: 2700N / 607lbf  
- Long Term: 890N / 200lbf  
Minimum bending radius:  
- Loaded: 20 x diameter  
- Unloaded: 10 x diameter  
Crush Resistance: 220N/cm

Impact Resistance: 25 Impacts (min.)  
Flexing,  $\pm 90^\circ$ : 25 Cycles (min.)  
Temperature Rating:  
Operation, -40°C to +70°C  
Installation, -40°C to +55°C  
Storage, -50°C to +70°C  
Twist Test: 25 Cycles (min.)

## Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available.

## Warranty Info

All warranty information can be viewed at [www.ree.com](http://www.ree.com).  
This product is RoHS compliant and is directive 2002/95/EC.  
It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.