


Part No.: 10-002-12C-AZNONF

10-002-12C-AZNONF

Scope

This document establishes the specification requirements for a multimode 50/125 general purpose duplex fiberoptic cable. This cable construction consists of multimode fibers in a duplex tight-buffered design with a riser rated PVC jacket suitable for indoors in the riser.



Applications

Riser Indoor

Applicable Documents

TIA/EIA FOTP Standards 455

- Color Coding of Fiber Optic Cables TIA/EIA-598

- UL 1666

- GR-409-CORE

Overall Cable Construction

- Tight Buffered Fiber
- Dimension: 900 μ m, nominal.
Tight buffered fiber color code: 1-blue, 2-orange
- Cable strength
Aramid yarns are pulled in with the tight-buffered fiber under the siamese outer jacket.
- Outer Sheath
Orange riser rated PVC jacket (or color per customer request)
- Cable Markings
REMFO 10 SERIES, FIBER OPTIC CABLE, 2-50/125, REMEE PRODUCTS CORP., MM/YY (month & year of manufacture), OFNR C(ETL)US, Sequentially meter marked.
- Special print as required by customer.

Fiber Attenuation

$\leq 3.0/1.0$ dB/km

Fiber Bandwidth

$\geq 500/500$ MHz-km

