


Part No.: 30-001-76E-RYNONP

## 30-001-76E-RYNONP

### Scope

This document establishes the specification requirements for a multimode SM OS2 general purpose simplex fiberoptic cable. This cable construction consists of multimode fiber in a simplex tight-buffered design with a plenum rated jacket suitable for indoors in the plenum space.



### Applications

Plenum Indoor

### Applicable Documents

- TIA/EIA FOTP Standards 455
- Color Coding of Fiber Optic Cables TIA/EIA-598
- UL 910
- GR-409-CORE

### Overall Cable Construction

- Tight Buffered Fiber
- Dimension: 900 $\mu$ m, nominal.  
Tight buffered fiber color code: 1-blue
- Cable strength  
Aramid yarns are pulled in with the tight-buffered fiber under the outer jacket.
- Outer Sheath  
Yellow riser rated Plenum jacket (or color per customer request)
- Cable Markings  
REMFO 30 SERIES, FIBER OPTIC CABLE, 1-SM OS2, REMEE PRODUCTS CORP., MM/YY (month & year of manufacture), OFNP C(ETL)US, Sequentially meter marked.
- Special print as required by customer.

### Fiber Attenuation

$\leq$ .40/0.30 dB/km

### Mechanical & Environmental Performance

- Storage Temperature Range  $\pm$ C -40 to +85
- Operating Temperature Range  $\pm$ C -0 to +85

