


Part No.: 27-XXX-12D-ABSXNF

27-XXX-12D-ABSXNF

Scope

This document establishes the specifications for a riser rated, indoor/outdoor, all dielectric, multimode laser optimized OM2, dry block fiber optic cable in a loose buffer tube design.



Applications

Riser Indoor or Outdoor in duct or aerial lashed

Applicable Documents

- TIA/EIA FOTP Standards 455
- Color Coding of Fiber Optic Cables TIA/EIA-598
- UL 1666
- GR-20-CORE

Overall Cable Construction

- Buffer tube

- High Modulus Polymeric material.

Dimension: 2.8 mm, nominal with the exception of the 4 fiber cable which is 2.2mm, nominal
Tube and fiber color code per EIA/TIA-598 or as specified by customer.

- Filling compound: A non-toxic and dermatological safe antioxidant hydrocarbon based gel.

Dielectric central strength member with water swellable yarns. An up-coat of polymer (if necessary per construction)

Cable Core:

The cable elements are stranded around the CSM, using reverse oscillation.

Moisture Resistance: A water blocking tape is applied over the cable core to prevent water ingress and migration with a nominal of 25% overlap.

- Non-wicking binder yarns are applied over the core tape.

Cable strength

Circumferential strength members are placed over the cable core and under the outer sheath.

- Outer Sheath

UV Resistant Black Riser Rated PVC. (or color per customer request)

A ripcord is applied under the outer sheath.

Cable Markings

REMFO 27 SERIES, FIBER OPTIC CABLE, # of fibers-50/125, OM2 10GIG, REMEE PRODUCTS CORP., MM/YY (Month & Year of manufacture), OFNR C(ETL)US, Sequentially marked.

- Special print as required by customer.

Fiber Attenuation



$\leq 3.0 / 1.0$ dB/km

Fiber Bandwidth

$\geq 750 / 500$ MHz-km

Mechanical & Environmental Performance

Maximum Tensile Load for:

- Installation: 2700N / 607lbf

- Long Term: 890N / 200lbf

Minimum bending radius:

- Loaded: 20 x diameter

- Unloaded: 10 x diameter

Crush Resistance: 220N/cm

Impact Resistance: 25 Impacts (min.)

Flexing, $\pm 90^\circ$: 25 Cycles (min.)

Temperature Rating:

Operation, -40°C to $+70^\circ\text{C}$

Installation, -20°C to $+55^\circ\text{C}$

Storage, -40°C to $+70^\circ\text{C}$

Twist Test: 25 Cycles (min.)

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available.

Warranty Info

All warranty information can be viewed at www.remee.com.

This product is RoHS compliant and is directive 2002/95/EC.

It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.