


Part No.: 11-XXX-76E-AYNOOF

11-XXX-76E-AYNOOF

Scope

This document establishes the specification requirements for a distribution indoor/outdoor, singlemode OS2 fiberoptic cable. This cable construction consists of singlemode fibers in a distribution tight-buffered design with a riser rated PVC jacket suitable for outdoors in duct, indoors in the riser and acceptable in tray installation as well.



Applications

Riser Indoor or Outdoor in duct

Applicable Documents

- TIA/EIA FOTP Standards 455
- Color Coding of Fiber Optic Cables TIA/EIA-598
- UL 1666
- GR-409-CORE


Overall Cable Construction

- Tight Buffered Fiber
- Dimension: 900 μ m, nominal.
Tight buffered fiber color code: 1-blue, 2-orange, 3-green, 4-brown, 5-slate, 6-white, 7-red, 8-black, 9-yellow, 10-violet, 11-rose, and 12-aqua.
- Cable strength
Aramid yarns with water swellable characteristics are pulled in with the tight-buffered fibers under the outer jacket.
- Outer Sheath
Pressure extruded yellow UV resistant riser rated PVC jacket (or color per customer request)
- Cable Markings
REMFO 11 SERIES, FIBER OPTIC CABLE, XX (No. of fibers)-SM, REMEE PRODUCTS CORP., MM/YY (month & year of manufacture), OFNR C(ETL)US, Sequentially meter marked.
- Special print as required by customer.

Fiber Attenuation

$\leq 0.40/0.30$ dB/km

Mechanical & Environmental Performance



Maximum Tensile Load for:

- Installation: 2&4-fiber 1405N/315lbf, 6&8-fiber 1610N/362lbf
 - 12-fiber 2700N/600lbf
 - Long Term: 2&4-fiber 455N/102lbf, 6&8-fiber 535N/120lbf
 - 12-fiber 600N/135lbf
- Minimum bending radius:**
- Loaded: 20 x diameter
 - Unloaded: 10 x diameter

- Impact Resistance:** 25 Impacts (min.)
- Flexing, $\pm 90^\circ$:** 25 Cycles (min.)
- Temperature rating:**
- Operation,** -40°C to $+85^\circ\text{C}$
- Installation,** 0°C to $+75^\circ\text{C}$
- Storage,** -55°C to $+85^\circ\text{C}$
- Crush Resistance:** 100N/cm

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available.

Warranty Info

All warranty information can be viewed at www.remee.com.
This product is RoHS compliant and is directive 2002/95/EC.
It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.