

22-6 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725228

Applications:

This document establishes the specifications for a plenum rated six conductor unshielded cable used for communication applications.

Construction Details:

Number of Conductors: 6/C

Conductor: 22AWG Stranded Bare Copper Insulation Material: Remguard Plenum Polymer

Nominal Insulation Thickness: 0.007 in.

Nominal Insulation Diameter: 0.043 in.

Color Code: Black, Blue, Green,

Brown, Natural, Red

Shield: N/A Drain: N/A

Jacket Material: Remguard Plenum Polymer

Nominal Jacket thickness: 0.015 in.

Nominal Diameter: 0.155 in.

Surface Print: 3122598 CMP 22AWG C(ETL)US FT6 + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 20 lbs. / 1,000 feet

Standards:

- NEC Article 800
- UL Subject 444, Type CMP

Codes & Listings:

• C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.






lssue Date: 06/15 All warranty information can be viewed at WWW.REMEE.COM. Revision: 1

This product is RoHS compliant to directive 2002/95/EC.

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



22-6 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725228

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Dotos	

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your





Issue Date: 06/15 Revision: 1 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.