

Part No.: 725901

Applications:

This document establishes the specifications for a composite cable individually and overall jacketed used for communication applications.

Component 1 Construction Details:

Number of Conductors: 4/C

Conductor: 18AWG Stranded Bare Copper. Insulation Material: Remguard Plenum Polymer Insulation Color Code: Black, Red, White, Green Jacket Material: Remouard Plenum Polymer

Jacket Color: Gray Rip Cord: Nylon

Nominal Diameter: 0.179 in.

Surface Print: 3122598 POWER LOCK CMP 4/18AWG C(ETL)US

ABCDE0123456789

Component 2 Construction Details:

Number of Pairs: 3 Pair

Conductor: 22AWG Stranded Bare Copper. Insulation Material: Remguard Plenum Polymer Insulation Color Code: Black paired with Red White paired with Green Orange paired with Brown

Overall Shield: Aluminum/Polyester Drain Wire: Stranded Tin Copper

Jacket Material: Remguard Plenum Polymer

Jacket Color: Orange Rip Cord: Nylon

Nominal Diameter: 0.200 in.

Surface Print: 3122598 CARD READER CMP 3P/22AWG C(ETL)US

ABCDE 0123456789

Component 3 Construction Details:

Number of Conductors: 4/C

Conductor: 22AWG Stranded Bare Copper. Insulation Material: Remguard Plenum Polymer Insulation Color Code: Black, Red, White, Green Jacket Material: Remguard Plenum Polymer

Jacket Color: White Rip Cord: Nylon

Issue Date: 04/16

Revision: 9

Nominal Diameter: 0.141 in.

Surface Print: 3122598 DOOR CONTACT CMP 4/22AWG C(ETL)US

ABCDE0123456789

Access Control Cable Plenum

ETL listed for guaranteed performance Made in the USA

Component 4 Construction Details:

Number of Conductors: 2/C

Conductor: 22AWG Stranded Bare Copper. Insulation Material: Remquard Plenum Polymer

Insulation Color Code: Black, Red

Jacket Material: Remouard Plenum Polymer

Jacket Color: Blue Rip Cord: Nylon

Nominal Diameter: 0.122 in.

Surface Print: 3122598 REX/SPARE CMP 2/22AWG C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9

Overall Construction Details:

Construction: Four components are cabled together

and overall jacketed

Jacket Material: Remguard Plenum Polymer

Nominal Jacket Thickness: 0.015 in.

Nominal Diameter: 0.410 in.

Surface Print: 3122598 ACCESS CONTROL CABLE

CMP 4/18AWG 12/22AWG C(ETL)US + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Operation: -2°C to 60°C

Nominal Weight:

99 lbs. / 1,000 feet

Codes & Listings:

NEC Article 800

UL Subject 444, Type CMP

C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.



Access Control Cable Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725901

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

mation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and



