



# 18-2 Unshielded Plenum

ETL listed for guaranteed performance  
Made in the USA

Part No.: 760180

## Applications:

This document establishes the specifications of a plenum rated two conductor twisted, unshielded cable used for fire protective signaling applications.

## Construction Details:

Number of Conductors: 2/C  
Conductor: 18AWG Solid Bare Copper  
Insulation Material: Remguard Plenum Polymer  
Nominal Insulation Thickness: 0.010 in.  
Nominal Insulation Diameter: 0.060 in.  
Color Code: Black, Red  
Jacket Material: Remguard Plenum Polymer  
Jacket Color: Red or Per Customer Requirement  
Nominal Jacket Thickness: 0.015 in.  
Nominal Diameter: 0.150 in.  
Surface Print: 3122598 FPLP 18AWG (ETL)US +  
Sequential Footage Marking

## Electricals:


Suggested Working Voltage: 300 Volts, rms.  
Direct Current Resistance: 6.39 Ohms/1000'@20°C

## Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 17 lbs. / 1,000 Feet



## Standards:

- NEC Article 760
- UL Subject 1424, Type FPLP

## Codes & Listings:

- (ETL)US

## Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.




Issue Date: 04/16  
Revision: 3

All warranty information can be viewed at [WWW.REMEE.COM](http://WWW.REMEE.COM).

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921  
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: [www.remee.com](http://www.remee.com)



# 18-2 Unshielded Plenum

ETL listed for guaranteed performance  
Made in the USA

Part No.: 760180

**Note:** While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. does not guarantee that it is error-free, nor does Remeë Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeë Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeë Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: \_\_\_\_\_  
Company: \_\_\_\_\_  
Date: \_\_\_\_\_



MADE IN THE USA



Issue Date: 04/16  
Revision: 3

All warranty information can be viewed at [WWW.REMEE.COM](http://WWW.REMEE.COM).

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921  
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: [www.remee.com](http://www.remee.com)