

Part No.: 900904

Applications:

This document establishes the specifications of a four conductor shielded cable used for communication applications.

Construction Details:

Number of Conductors: 4/C Conductor: 16AWG Stranded Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008 in. Nominal Insulation Diameter: 0.074 in. Color code: Black, White, Red, Green Shield: Aluminum/Polyester Tape (100% Coverage) Drain: Stranded Tin Copper Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.015 in. Nominal Diameter: 0.212 in. Surface Print: 3122598 CMR 16AWG C(ETL)US FT4 + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.


Technical Details:

Temperature Rating

	Operation:	-20°C to +60°C
Nominal Weight:		48 lbs. / 1,000 feet

16-4 Shielded Non-Plenum

ETL listed for guaranteed performance Made in the USA



Standards:

- NEC Article 800
- UL Subject 444
- CMR Type FT4

Codes & Listings:

C(ETL)US CMR

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 06/15 Revision: 3 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



16-4 Shielded Non-Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: 900904

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and
agreed to this specification sheet and upon confirma-
tion of your order; this item may be non-cancelable
and non-returnable.

Signature:

Company:

Date:





Issue Date: 06/15 Revision: 3 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com