

22-2 Shielded 18-1 Unshielded 12-2 Unshielded Plenum

Part No.: LUGRX46LP

Applications:

This document establishes the specifications for a composite cable used for power limited applications.

Construction Details:

Number of Conductors: 2/C (1 pair)
Conductor: 22AWG Stranded Bare Copper
Insulation Material: FEP
Nominal Insulation Thickness: 0.012 in.
Nominal Insulation Diameter: 0.053 in.
Color Code: White paired with Green
Shield: Aluminum/Polyester Tape (100% Coverage)
Drain: Tin Copper

Number of Conductors: 1/C
Conductor: 18AWG Stranded Bare Copper
Insulation Material: Remguard
Nominal Insulation Thickness: 0.008 in.
Nominal Insulation Diameter: 0.062 in.
Color Code: Orange

Number of Conductors: 2/C
Conductor: 12AWG Stranded Bare Copper
Insulation Material: Remguard
Nominal Insulation Thickness: 0.009 in.
Nominal Insulation Diameter: 0.118 in.
Color Code: Red, Black

Jacket Material: Remguard
Jacket Color: Per Customer Requirement
Nominal Diameter: 0.325 in.
Surface Print: 3122598 CL3P 2C12 2C22 1C18
(ETL)US + Sequential Footage Marking

Issue Date: 07/18
Revision: 1

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

Electricals:

Suggested Working Voltage: 150 V RMS

Max. Capacitance Cond-Cond: 25pF/FT

Technical Details:

Temperature Rating

Operation -2°C to +75°C

Nominal Weight: 72 Lbs. / 1,000 ft.

Standards:

- National Electric Code - Article 725
- UL Subject 13


Codes & Listings:

- (ETL)US CL3P

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





22-2 Shielded
18-1 Unshielded
12-2 Unshielded
Plenum

Part No.: LUGRX46LP

Note: While Remeewire Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeewire Products Corp. does not guarantee that it is error-free, nor does Remeewire Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeewire Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeewire Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____
Company: _____
Date: _____

Issue Date: 07/18
Revision: 1

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

