

Part No.: NY516ST

Applications:

This document establishes the specifications for a two conductor shielded cable used for Local Law #5/73 fire alarm installations.

Construction Details:

Number of Conductors: 2/C

Conductor: 16AWG Solid Bare Copper.

Insulation Material: FEP

Nominal Insulation Thickness: 0.016" Nominal Insulation Diameter: 0.082"

Color Code: Black, Red

Shield: Aluminum/Polyester Tape (100 %Coverage)

Drain: Tin Copper Jacket Material: FEP Jacket Color: Red

Nominal Jacket Thickness: 0.026"

Nominal Diameter: 0.220"

Surface Print: REMEE PRODUCTS CORP. TYPE

FPLP 16AWG SHIELDED 200°C (ETL)US ALSO CLASSIFIED NYC CERT. FIRE ALARM CABLE + SEQUENTIAL FOOTAGE

MARKING


Electricals:

Suggested Working Voltage: 300 Volts, rms. Direct Current Resistance: 4.01 ohms/1000'@25°C

Nominal Capacitance: 27 pF/ft.

16-2 Shielded Local Law #5/73 Fire

Alarm ETL listed for guaranteed performance Made in the USA



Technical Details:

Temperature Rating

Operation -20°C to 200°C

Nominal Weight: 42 lbs. / 1,000 ft.

Standards:

- National Electric Code—Article 760 Type FPLP
- Building Code City of New York
- Certified For Use In New York City
- Complies With City of New York Technical Policy & Procedure Notice #2/95

Codes & Listings:

- UL Subject 1424
- (ETL)US FPLP

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 06/15 Revision: 4

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



16-2 Shielded Local Law #5/73 Fire

Alarm ETL listed for guaranteed performance Made in the USA

Part No.: NY516ST

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

specification shee	onstitutes that you have read and agreed to this et and upon confirmation of your order; this cancelable and non-returnable.
Signature:	
Company:	
Date:	





Issue Date: 06/15 Revision: 4

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.