

RG-59/U + 2C18 Polyethylene

Made in the USA

Part No.: R001539WBPOLY

Description:

This document establishes the specifications for a cable containing a RG-59/u and two conductors unshielded with an overall water swellable tape and polyethylene jacket.

Construction Details (18/2):

Conductor: 18AWG Stranded Bare Copper
Insulation Material: Polyvinyl Chloride
Nominal Insulation Thickness: 0.014 in.
Nominal Insulation Diameter: 0.074 in.
Color Code: Black, Red


Construction Details (RG-59/U):

Conductor: 20AWG Solid Bare Copper
Dielectric Material: Cellular Polyethylene.
Nominal Dielectric Core O.D.: 0.145 in.
Braid Shield: CCA
Jacket Material: Polyvinyl Chloride
Nominal Jacket Diameter: 0.234 in.
Jacket Color: Black

Electricals (RG59/U):

Nominal Characteristic Impedance: 75 Ω
Nominal Capacitance: 17.3 pF/ft
Nominal Velocity of Propagation: 78%
Nominal Attenuation per 100 ft:

2.10 dB	@	50 MHz	6.30 dB	@	500 MHz
2.60 dB	@	100 MHz	8.50 dB	@	900 MHz
4.00 dB	@	200 MHz			



*Drawing Not To Scale

Construction Details (Overall):

Construction Type: RG-59/U and two 18AWG conductors are cabled on a SZ machine (oscillating twist) with a water swellable tape over core

Jacket Material: Polyethylene

Nominal Jacket Thickness: 0.025 in.

Nominal Cable Dimensions: Minor: 0.234 in.

Major: 0.370 in.

*Cable will not be round

Jacket Color: Black

Surface Print: RG59/U 75 OHM + 2/18AWG

SUITABLE FOR DIRECT BURIAL +
Sequential Footage Marking

Technical Details:

Temperature Rating

Operation: -20°C to +60°C

Nominal Weight:


65 lbs. / 1,000 ft

Codes & Listings

- Non-Listed

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



RG-59/U + 2C18 Polyethylene

Made in the USA

Part No.: R001539WBPOLY

Note: While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. does not guarantee that it is error-free, nor does Remeë Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeë Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeë Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____
Company: _____
Date: _____

Issue Date: 06/15
Revision: 2

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



MADE IN THE USA