


This document establishes the specifications for a

communication and low loss microphone cable.

24-2 Braid Shield Microphone Cable Non-Plenum

Ultra flexible PVC Jacket Bare Copper Braid Shield

Low-loss PE Insulation-



Technical Details:

Temperature Rating

Operation	-40°C to +80°C
Installation	-20°C to +80°C
Nominal Weight:	38 lbs. / 1,000 ft.

Codes & Listings:

NonListed

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 01/20 Revision: 1 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

PO Box 488 468 RT17A Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

Construction Details:

two conductor braided cable used for

Part No.: 2C24LLM

Applications:

Number of Conductors: 2/C Conductor: 24AWG 41/40 Stranded Bare Copper Insulation Material: Polyethylene Nominal Insulation Thickness: 0.013 in. Color Code: Black, White Fillers: Fibrillated Polypropylene Braid Shield. 36AWG Bare Copper 95% Coverage Jacket Material: Polyvinyl Chloride Nominal Jacket Diameter: 0.236 in. Jacket Color: Matte Black Surface Print: REMEE PRODUCTS 2/C 24AWG LOW LOSS MICROPHONE CABLE MADE IN USA

Electricals:

Suggested Working Voltage: 300 Volts, rms. Nominal Capacitance Cond-Cond: 20 pF/FT



24-2 Braid Shield Microphone Cable Non-Plenum

Part No.: 2C24MC

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this
specification sheet and upon confirmation of your order. The
Remee Wire & Cable warranty is an integral part of this specifica-
tion. This item may be non-cancelable and non-returnable.

Signature:

0

Company:

Date:



Issue Date: 01/20 Revision: 2

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

PO Box 488 468 RT17A Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com