


Part No.: 5333-EL

Applications:

This document establishes the specifications for a plenum rated two conductor unshielded cable used for communication applications.

Component 4 Type EL - Lock:

Number of Conductors: 2/C Conductor: 18AWG Stranded Bare Copper. Insulation Material: 0.008in. Low Smoke Polyvinylchloride Insulation Color Code: Red, Black Jacket Material: Low Smoke Polyvinylchloride Jacket Color: Pink Rip Cord: Nylon Nominal Diameter: 0.154 in. Surface Print: VIGILANCE™ by REMEE 5333-EL (Logo) - LOCK CMP 2/18AWG c(ETL)us A B C D E 0 1 2 3 4 5 6 7 8 9



Electricals:

Suggested Working Voltage: 300 Volts, rms. DC Resistance: 6.5 Ohms/1000ft

Technical Details:

Temperature Rating:

Nominal Weight:

Codes & Listings:

- UL Subject 444, Type CMP
- C(ETL)US

-20°C to 60°C

17 lbs. / 1,000 feet



Issue Date: 12/20 Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

Access Control Cable Plenum

ETL listed for guaranteed performance Made in the USA



Access Control Cable Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: 5333-EL

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your or- der; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	



Issue Date: 12/20 Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.