


Part No.: 725105/95BC

Applications

This document establishes the specifications for a plenum rated RG6/U, 75 ohm, coaxial cable used for computers, broadcast and CCTV applications.

RG6 Coaxial Cable Plenum

ETL listed for guaranteed performance Made in the USA



Construction Details

Center Conductor: 18AWG Solid Bare Copper Dielectric Material: Foamed FEP Nominal Dielectric Core O.D: 0.176 in. 1st Shield: Bare Copper Braid Jacket Material: Remguard Plenum Polymer Nominal Overall Diameter: 0.245 in Jacket Color: Per Customer Requirement Surface Print: 3122598 CMP RG6/U TYPE 18AWG C(ETL)US FT6 + Sequential Footage Marking

Electricals

Nominal Capacitance: 17.3 pF/ft. Nominal Characteristic Impedance: 75 Ω Nominal Velocity of Propagation: 78% Nominal Attenuation per 100 ft.: 1.5 dB @ 50 MHz 2.1 dB @ 100 MHz 3.0 dB @ 200 MHz 4.5 dB @ 400 MHz 6.4 dB @ 700 MHz 7.9 dB @ 900 MHz

Technical Details

Temperature Rating

	Operation:	-2°C to +60°C
Nominal Weight:		45 lbs. / 1,000 ft.

Standards

- NEC Article 800
- Type CMP Rating FT6

Codes & Listings

C(ETL)US CMP

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 06/15 Revision: 5

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com



RG6 Coaxial Cable Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: 725105/95BC

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and
agreed to this specification sheet and upon confirma-
tion of your order; this item may be non-cancelable
and non-returnable.

Signature:

Company:

Date:



Issue Date: 06/15 Revision: 5 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com