



18-2 Shielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 760181

Applications:

This document establishes the specifications of a plenum rated two conductor twisted, shielded cable used for fire protective signaling applications.

Construction Details:

Number of Conductors: 2/C
 Conductor: 18AWG Solid Bare Copper
 Insulation Material: Remguard Plenum Polymer
 Nominal Insulation Thickness: 0.010 in.
 Nominal Insulation Diameter: 0.060 in.
 Color Code: Black, Red
 Shield: Aluminum/Polyester Tape (100% coverage)
 Drain: Tinned Copper
 Jacket Material: Remguard Plenum Polymer
 Jacket Color: Red or Per Customer Requirement
 Nominal Jacket Thickness: 0.015 in.
 Nominal Diameter: 0.155 in.
 Surface Print: 3122598 FPLP 18AWG SHIELDED
 (ETL)US + Sequential Footage
 Marking

Electricals:


Suggested Working Voltage: 300 Volts, rms.
 Direct Current Resistance: 6.39 Ohms/1000' @20°C

Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 19 lbs. / 1,000 Feet



Standards:

- NEC Article 760
- UL Subject 1424, Type FPLP

Codes & Listings:

- (ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Issue Date: 04/16
Revision: 3

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



18-2 Shielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 760181

Note: While Remeewire Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeewire Products Corp. does not guarantee that it is error-free, nor does Remeewire Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeewire Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeewire Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____

Issue Date: 04/16
Revision: 3

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com