

Part No.: B1P22TFOSTB

Applications:

This document establishes the specifications for a 2C (1 pair) cable EIA-RS485 data grade with a foil plus braid shield. For RS-485 as well as DMX-512 and other computer control applications.

Construction Details:

Number of Conductors: 2/C (1 Pair) Conductor: 22AWG Str Tinned Copper Insulation Material: Foam Polyethylene Nominal Insulation Thickness: 0.025 in. Color Code: Blue & White Shield: Aluminum/Mylar Tape (Foil Facing Out) 24AWG Str. Tinned Copper Drain: **Tinned Copper Braid** Braid: Minimum Braid Coverage: 65% **PVC** Jacket Material: Jacket Color: Black Nominal Jacket Thickness: 0.041 in. Nominal Overall Diameter: 0.281 in. Surface Print:

REMEE TEKwire™ RS-485 1PR 22 AWG SHIELDED 3122598 C(ETL)US CM OR PLTC SUN RES FT1 ROHS COMPLIANT MADE IN USA (Lot #) +


Sequential Footage Marking

Electricals:

Issue Date: 07/20

Revision: 7

22 AWG-1Pr Shielded RS-485



Technical Details:

Temperature Rating -20°C to +60°C

Nominal Weight: 43 lbs. / 1,000 ft.

Maximum Pulling Tension 60 lbf

Minimum Bending Radius 3.0 in

Standards:

- EIA RS-485
- National Electric Code Articles 725 and 800
- UL Standard 444
- UL Standard 13
- UL 1581

Codes & Listings

- CM, PLTC
- C(ETL)US CM OR PLTC

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



22 AWG-1Pr Shielded RS-485

Part No.: B1P22TFOSTB

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

tion of your order; this item may be non-cancelable and non-returnable.
Signature:
Company:
Date:

Your signature constitutes that you have read and





Issue Date: 07/20 Revision: 7 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com