

Part No.: B1P24TOSTB

Applications:

This document establishes the specifications for a 1200hm, one pair cable with a foil plus braid shield. The insulation is PE, and jacket is PVC. This is an EIA RS-485 computer cable for those applications as well as DMX-512.


Construction Details:

Number of Conductors: Conductor: Insulation Material:		2/C (1 Pair) 24AWG Str Tinned Copper Polyethylene		
Nominal Insulation Thicknes				
Color Code:		Blue / White		
Shield:	Aluminum/	Mylar Tape (Foil Facing Out)		
Drain:		24AWG Str. Tinned Copper		
Braid:		Tinned Copper Braid		
Minimum Braid:		Coverage: 90%		
Jacket Material:		PVC		
Jacket Color:		Gray		
Nominal Jacket Thickness:		0.020 in.		
Nominal Overall Diameter:		0.203 in.		
Surface Print:				
REMEE PRODUCTS CORP. RS-485 3122598 CM				
24AWG 1/P SHIELDED C(ETL)US ROHS				
COMPLIANT MADE IN USA (Lot #) + Sequential				
Footage Marking				

Electricals:

Maximum Operating Voltage:	300 Volts RMS
Conductor DCR: (Maximum)	27.7Ω / Mft
Capacitance, Nominal Cond to cond	12.8 pF/ft
Cond-shield	23 pF/ft
Impedance, Nominal	120Ω
Velecity of propagation (Nom.)	66%

24 AWG-1Pr Shielded RS-485 120Ω CM



Technical Details:

Temperature Rating UL Temp	-20°C to +75°C +60°C
Nominal Weight:	34 lbs. / 1,000 ft.
Maximum Pulling Tension	65 lbf
Minimum Bending Radius	2.5 in

Standards:

- EIA RS-485
- National Electric Code Article 800
- UL Standard 444
- UL 1581

Codes & Listings

- CM Rating
- C(ETL)US CM

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/20 Revision: 6

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



24 AWG-1Pr Shielded RS-485 120Ω CM

Part No.: B1P24TOSTB

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date: -



Issue Date: 06/20 Revision: 6

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com