

Part No.: CH1026F

Applications:

This document establishes the specifications for a two conductor cable used in audio applications.

Construction Details:

Number of Conductors: 2/C

Conductor: 12AWG Stranded Bare Copper Insulation Material: Polyvinyl Chloride

Insulation Thickness: 0.015 in. Insulation Diameter: 0.120 in. Color Code: Black, Red

Jacket Material: Polyvinyl Chloride

Jacket Color: White or Per Customer Requirement

Jacket Thickness: 0.020 in. Nominal Diameter: 0.280 in

Surface Print: 3122598 HI-STRAND AUDIO


CABLE CSA C(ETL) FT4 2 COND 12AWG 105 STRAND 75°C CL3R (ETL)US MADE IN USA...SUITABLE FOR OUTDOOR USE...OXYGEN FREE COPPER MADE IN USA + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 150 Volts, rms.

12-2 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance Made in the USA



Technical Details:

Temperature Rating

Operation: -20°C to + 75°C

Nominal Weight: 65 lbs. / 1,000 ft.

Standards:

- NEC Article 725
- CL3R Rating FT4

Codes & Listings:

- (ETL)US CL3R
- C(ETL) FT4

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







Issue Date: 03/18 Revision: 0 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



12-2 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: CH1026F

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Datas	

Your signature constitutes that you have read and agreed to







Issue Date: 03/18 Revision: 0 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com