



22-2 Shielded 18-2 Unshielded Plenum

Part No.: LUGRX346SP

Applications:

This document establishes the specifications for a two pair, one pair shielded cable used for communication applications.

Construction Details:

Number of Conductors: 4/C (2 pair)
Conductor: 22AWG Stranded Bare Copper.
Insulation Material: FEP
Nominal Insulation Thickness: 0.012 in.
Nominal Insulation Diameter: 0.053 in.
Color Code: White paired with Blue
Shield: Aluminum/Polyester Tape (100% Coverage)
Drain: 24AWG 7/32 Tin Copper

Conductor: 18AWG Stranded Bare Copper.
Insulation Material: Remguard
Nominal Insulation Thickness: 0.010 in.
Nominal Insulation Diameter: 0.068 in.
Color Code: Black, Red

Jacket Material: Remguard
Jacket Color: White with Green Stripe
Nominal Diameter: 0.190 in.
Surface Print: PLENUM 2/C 18 + 2/C 22 SHIELDED
C(ETL)US CMP 3122598 MADE IN USA
+ Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 V RMS
Cap. Cond-Cond 22AWG: 25 pF/FT Max.

Technical Details:

Temperature Rating

Operation -2°C to +75°C

Nominal Weight: 48 Lbs. / 1,000 ft.

Standards:

- National Electric Code - Article 800
- UL Subject 444

Codes & Listings:

- C(ETL)US CMP FT6

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



MADE IN THE USA




Issue Date: 07/18
Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



22-2 Shielded
18-2 Unshielded
Plenum

Part No.: LUGRX346SP

Note: While Remeewire Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeewire Products Corp. does not guarantee that it is error-free, nor does Remeewire Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeewire Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeewire Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____



MADE IN THE USA



Issue Date: 07/18
Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com