

16-2 Pair Unshielded Local Law #39 Fire Alarm

ETL listed for guaranteed performance
Made in the USA

Part No.: NY16PUT

Applications:


This document establishes the specifications for a two pair unshielded cable used for Local Law #39 fire alarm installations.

Construction Details:

Number of Conductors: 4/C (2 Pair)
 Conductor: 16AWG Solid Bare Copper.
 Insulation Material: FEP
 Nominal Insulation Thickness: 0.016"
 Nominal Insulation Diameter: 0.082"
 Color Code: Pair #1, Black/Red
 Pair #2, Black/White
 Shield: N/A
 Drain: N/A
 Jacket Material: FEP.
 Jacket Color: Red
 Nominal Jacket Thickness: 0.026"
 Nominal Diameter: 0.323"
 Surface Print: VIGILANCE™ by REMEE TYPE
 FPLP 16AWG 200°C (ETL)US ALSO
 CLASSIFIED NYC CERT. FIRE ALARM CABLE
 LL39 MADE IN USA + SEQUENTIAL FOOTAGE
 MARKING

Electricals:

Suggested Working Voltage: 300 Volts, rms.
 Direct Current Resistance: 4.09 Ω/1000' @25°C
 Nominal Capacitance: 15.2 pF/ft.
 Insulation Resistance: >100 Megohms/1M' @ 60°C
 Nominal Impedance: 97 Ω



Technical Details:

Temperature Rating	Operation	-20°C to 200°C
Nominal Weight:	70 lbs. / 1,000 ft.	

Standards:

- National Electric Code—Article 760 Type FPLP
- Building Code City of New York
- Certified For Use In New York City, Local Law No. 39
- NFPA 262

Codes & Listings:

- UL Subject 1424
- (ETL)US FPLP



MADE IN THE USA




Issue Date: 12/21
Revision: 5

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



16-2 Pair Unshielded Local Law #39 Fire Alarm

ETL listed for guaranteed performance
Made in the USA

Part No.: NY16PUT

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — **M for 1000 feet**, and **L for 500 feet**
Available Put-Up's — **1 for Reel**, and **2 for Box**
Available Jacket Color — **R for Red**

These 3-place designators are placed at the end of the specific part number for LL39 compliant parts to fully describe the individual packaging and length.

Note: While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. does not guarantee that it is error-free, nor does Remeë Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeë Products Corp. reserves the right

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____
Company: _____
Date: _____



MADE IN THE USA



Issue Date: 12/21
Revision: 5

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remeë.com