

# RG-59/U Coaxial Cable Polyethylene Jacket

Part No.: R001510WBTPOLY

## **Applications**

This document establishes the specifications for an RG-59/U type coaxial cable with a waterblock tape and UV resistant polyethylene jacket used for Broadcast and MATV applications.

#### **Construction Details**

Center Conductor: 20AWG Solid Bare Copper Dielectric Material: Cellular Polyethylene Nominal Dielectric Core O.D: 0.146 in.

Shield: CCA braid
Tape: Waterblocking Tape
Jacket Material: Polyethylene
Nominal Overall Diameter: 0.242 in.
Jacket Color: Black UV resistant


Surface Print: RG59 95% BURIAL/WET LOCATIONS +

Sequential Footage Marking

# **Electricals**

Nominal Capacitance: 17.3 pF/ft. Nominal Characteristic Impedance: 75 ohms Nominal Velocity of Propagation: 78% Nominal Attenuation per 100 ft.:

2.7 dB @ 100 MHz 3.8 dB @ 200 MHz 6.3 dB @ 500 MHz 8.5 dB @ 900 MHz



#### **Technical Details**

Temperature Rating

Operation: -20°C to +60°C

Nominal Weight: 23 lbs. / 1,000 feet

## Codes & Listings

Non-Listed

#### **Preparation For Shipment**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/15 Revision: 4 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

Page 1 of 2



# RG-59/U Coaxial Cable Polyethylene Jacket

Part No.: R001510WBTPOLY

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and agreed to



Issue Date: 06/15 Revision: 4 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com