



# RG-11/U Coaxial Cable Non-Plenum

ETL listed for guaranteed performance

Part No.: R001582R

## Applications


This document establishes the specifications for an RG-11/U Type 75 ohm coaxial cable used for video display and CATV broadcast applications.

## Construction Details

Center Conductor: 14AWG Solid Bare Copperweld  
 Dielectric Material: Cellular Polyethylene  
 Nominal Dielectric Core O.D: 0.285 in.  
 Shield: CCA Braid (95% Coverage Nominal)  
 Jacket Material: Polyvinyl Chloride  
 Nominal Overall Diameter: 0.405 in.  
 Jacket Color: Black UV Resistant  
 Surface Print: 3122598 RG11/U TYPE 14AWG CMR  
 C(ETL)US FT4 MADE IN USA + Sequential  
 Footage Marking

## Electricals

Nominal Capacitance: 17.3 pF/ft  
 Nominal Characteristic Impedance: 75 ohms  
 Nominal Velocity of Propagation: 78%  
 Nominal Attenuation per 100 feet:  
 1.32 dB @ 100 MHz  
 2.06 dB @ 200 MHz  
 3.19 dB @ 400 MHz  
 5.07 dB @ 1000 MHz



## Technical Details

Temperature Rating	Operation: -20°C to +60°C
Nominal Weight:	87 lbs. / 1,000 feet

## Standards

- NEC Article 800
- CMR Rating

## Codes & Listings

- C(ETL)US CMR FT4

## Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.




Issue Date: 08/17  
 Revision: 0

All warranty information can be viewed at [WWW.REMEE.COM](http://WWW.REMEE.COM).

This product is RoHS compliant to directive 2002/95/EC .

1751 State Rte 17A STE #1 Florida, NY 10921  
 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: [www.remee.com](http://www.remee.com)



# RG-11/U Coaxial Cable Non-Plenum

ETL listed for guaranteed performance

Part No.: R001582R

**Note:** While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. does not guarantee that it is error-free, nor does Remeë Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeë Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeë Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: \_\_\_\_\_

Company: \_\_\_\_\_

Date: \_\_\_\_\_



Issue Date: 08/17  
Revision: 0

All warranty information can be viewed at [WWW.REMEE.COM](http://WWW.REMEE.COM).

This product is RoHS compliant to directive 2002/95/EC .

1751 State Rte 17A STE #1 Florida, NY 10921  
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: [www.remee.com](http://www.remee.com)