

Part No: RG11HDSDI

# RG11 6 GHz - 4K Digital Video Coax Riser

ETL listed for guaranteed performance Made in the USA



This document establishes the specifications for a precision RG 11/U Type 75 ohm coaxial cable 6 GHz—4K used for HD/SDI, standard SDI or high resolution video applications.

### **Construction Details**

Center conductor: 14AWG Solid Bare Copper Dielectric: Cellular Polyethylene 0.285 in OD

1st shield: Coaxial Shielding Tape

2nd shield: Tin Copper Braid 95% Coverage

Jacket material: Polyvinyl Chloride Nominal Diameter: 0.405 in.

Jacket Color: Per Customer Requirement

Surface Print: 3122598 RG11/U PRECISION VIDEO COAX

TYPE CMR 14AWG C(ETL)US FT4 SWEPT TO


6.0 GHZ MADE IN USA + Sequential Footage Marking

#### **Electricals**

Capacitance: 16.1 pF/ft, nominal

Characteristic impedance: 75 ohms, nominal Velocity of propagation: 84% nominal Conductor DC Resistance: 2.5 ohms/1M' Return Loss: >23 dB (1 MHz—1.5 GHz) >21 dB (1.5 GHz—4.5 GHz)

>21 dB (1.5 GHz—4.5 GHz) >15 dB (4.5 GHz—6.0 GHz)



Technical Details	
Operating Temperature	-30°C to 75°C
Wt/1M'	104 lbs.
Bend radius	4.0" Min.
Pulling Tension	83 lbs. Max.

## **Codes & Listings**

C(ETL)US CMR FT4

Frequency	1 MHz	3.6 MHz	10 MHz	71.5 MHz	135 MHz	270 MHz	360 MHz	720 MHz	1 GHz	1.5 GHz	2.25 GHz	3 GHz	4.5 GHz	6 GHz
Attenuation dB/100 feet	0.14	0.28	0.43	1.0	1.4	1.9	2.2	3.3	3.9	4.8	5.8	6.7	8.8	11.3
Attenuation dB/100 meters	0.46	0.92	1.4	3.3	4.6	6.2	7.2	10.8	12.8	15.7	19.0	22.0	28.9	37.1

Data rate	270 Mb/s SMPTE 259	360 Mb/s SMPTE 259	1.5 Gb/s SMPTE 292	3 Gb/s SMPTE 424		Dual-link 6Gb/s SMPTE ST-2081-1	Quad –LINK 12 Gb/s SMPTE ST2082
Max. Distance (typical)	2046'	1834'	521' - 849'	366' - 570'	529'	780'	780'





Issue Date: 04/19 Revision: 0 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

PO Box 488 468 RT17A Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



# RG11 6 GHz - 4K Digital Video Coax Riser

ETL listed for guaranteed performance Made in the USA

Part No.: RG11HDSDI

### **Preparation For Shipment**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

	e non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and agreed to





Issue Date: 04/19 Revision: 0 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

PO Box 488 468 RT17A Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com