

Part No.: RMMS5AE350+1006

Applications:

This document establishes the specifications for a cable containing one Category 5e and a two conductor 18AWG cable in a siamese construction with a polyvinyl chloride jacket.

2c18 Construction Details:

Conductor: 18AWG Stranded Bare Copper Number of Conductors: 2/C Insulation Material: Polyvinyl Chloride Insulation Color: Black, Red

Cat5e Construction Details:


Conductor: 24AWG Solid Bare Copper. Number of Conductors: 4 Pairs (8/C) Insulation Material: Polyethylene.

Overall Cable Construction Details:

Construction Type: One Cat5e and one 2c18AWG are pulled in parallel at extrusion in a siamese construction. Jacket Material: Polyvinyl Chloride Jacket Color: Per Customer Requirement Nominal Jacket Thickness: 0.025 in. Nominal Overall Diameter: Minor over Cat5e: 0.210 in. Minor over 2c18: 0.182 in. Major: 0.417 in.

Category 5e + 18/2 Siamese Non-Plenum

ETL listed for guaranteed performance Made in the USA



Standards:

- NEC Article 800
- ANSI/TIA/EIA 568C.2 Category 5e

Codes & Listings:

- CMR Rating FT4
- C(ETL)US

Electrical Parameters (Cat5e):

Nominal Mutual Capacitance:	14 pF/ft							
Maximum Capacitance Unbalance	ce: 330 pF/ft							
Velocity of Propagation:	70%							
Max. Conductor D.C.R.:	28.6 ohm/1000 feet							
Max. DCR Unbalance:	5%							
Max. Delay Skew:	45.0 ns/100m							
Characteristic Impedance: from 0.772 - 100 MHz 100 \pm 15%								
from	101 - 250 MHz 100 ± 22%							
from	251 - 350 MHz 100 ± 32%							



Issue Date: 06/15 Revision: 3

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



Category 5e + 18/2 Siamese Non-Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: RMMS5AE350+1006

Electrical Characteristics (Cat5e):

Frequency	SRL	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	23.0	20.0	2.0	65.3	62.3	63.8	60.8	63.3	60.3
4	23.0	20.3	4.0	56.3	53.3	51.7	48.7	52.3	49.3
8	23.0	20.5	5.7	51.8	48.8	45.7	42.7	46.1	43.1
10	23.0	25.0	6.4	50.3	47.3	43.8	40.8	43.9	40.4
16	23.0	25.0	8.2	47.3	44.3	39.7	36.7	39.1	36.1
20	23.0	25.0	9.2	45.8	42.8	37.7	34.7	36.6	33.6
25	22.0	25.0	10.4	44.3	41.3	35.8	32.8	33.9	30.9
31.25	21.1	23.6	11.7	42.9	39.9	33.9	30.9	31.2	28.2
62.5	18.1	21.5	16.9	38.4	35.4	27.8	24.8	21.5	18.5
100	16.0	20.1	21.9	35.3	32.3	23.8	20.8	13.4	10.4
250	12.0	17.3	36.8	34.3	32.3	15.8	12.8		
300	11.2	16.8	40.9	33.2	31.2	14.2	11.2		
350	10.6	16.3	44.8	32.2	30.2	12.9	9.9		

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/15 Revision: 3 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



Category 5e + 18/2 Siamese Non-Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: RMMS5AE350+1006

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:



Issue Date: 06/15 Revision: 3

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com