

Part No.: 900942

Applications:

This document establishes the specifications for a two conductor riser-rated shielded cable used for communication applications.

Construction Details:


Number of Conductors: Two (2) Conductor: 22AWG Stranded bare copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008" Nominal Insulation Diameter: 0.045" Color code: Black, Red Shielding: Overall Aluminum/Polyester (100% coverage) Drain: Stranded tin copper Jacket material: Polyvinyl Chloride Jacket Color: Gray (Others with MOQ) Nominal Jacket Thickness: 0.015" Nominal Diameter: 0.124" Surface Print: VIGILANCE[™] by REMEE CMR/ FPLR 22AWG C(ETL)US FT4 MADE IN USA RoHS + Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms. Nom. Capacitance: 75pF/FT Nom. Velocity of Propagation: 55% Nom. Impedance: 33 Ohms Nom. DC Resistance17.5 Ohms/1M'

22-2 Shielded Riser

ETL listed for guaranteed performance Made in the USA



*Drawing not to scale

Technical Details:

Temperature Rating

-20°C to +60°C

Operation

Nominal Weight: 11

11 lbs./1,000 Ft.

Standards:

- National Electric Code Article 800, 760
- UL Subject 444, Type CMR FT4
- UL Subject 1424, Type FPLR

Codes & Listings:

C(ETL)US CMR



Issue Date: 04/22 Revision: 5 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com



22-2 Shielded Riser

ETL listed for guaranteed performance Made in the USA

Part No.: 900942

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — M for 1000 feet, and L for 500 feet Available Put-Up's — 1 for Reel, and 2 for Box Available Jacket Color — G for Gray, (Other Colors Available with Minimum Order Quantities)

These 3-place designators are placed at the end of the specific part number to fully describe the individual packaging and length.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

| agreed to this | e constitutes that you have read and specification sheet and upon confirma- der; this item may be non-cancelable nable. | |
|----------------|--|----|
| Signature: | | |
| Company: | | |
| Date: | | |
| | MADE IN THE USA | ¢, |

Issue Date: 04/22 Revision: 5 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.