

Part No.: 6B234STPENH

Applications

Supports all category 6 applications including Ethernet 100BASE -TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth applications such as 622 ATM, Wideband, Ethernet 1000BASE-T and emerging applications with anticipated data rates to 3.2 Gbps.

Construction Details:

No. 23 AWG solid bare copper conductor insulated with FEP. Two colored mated insulated conductors twisted together to form a pair and four pairs assembled around a pair separator to form a core. The core is overall shielded and jacketed with a low smoke flame retardant PVC.

Surface Print: ETL VERIFIED CAT6 TO TIA-568C.2...3122598 CMP 23AWG 4STP C(ETL)US 550 MHZ FT6 MADE IN USA

Color Code:

Pair	Color Code
1	Blue with White
2	Orange with White
3	Green with White
4	Brown with White

Electrical Parameters:

Mutual Capacitance: 14 pF/ft nominal

Capacitance Unbalance: 330 pF/100m maximum

Velocity of Propagation: 72%

Max. Conductor D.C.R.: 28.6 ohm/1,000 feet

Max. DCR Unbalance: 5%

Customer Service: 800-431-3864

Max. Delay Skew: 45.0 ns/100m

Characteristic Impedance: from 0.772 - 100 MHz 100 \pm 15%


from 101 - 250 MHz 100 \pm 22%

from 251 - 550 MHz 100 ± 32%

Category 6 Shielded 550MHz Plenum

ETL verified for guaranteed performance

Made in the USA



Technical Details

Temperature Rating

l	nstallation:	-0°C to 50°C
	Operation:	-2°C to 60°C
Nominal Diameter:		0.280 in.
Nominal Cable Weight:		40 lbs/1,000 feet

Standards

- ANSI/TIA/EIA 568C.2 Category 6
- National Electric Code Article 800
- UL Subject 444

Codes & Listings

- CMP Rating FT6
- ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 6
- C(ETL)US CMP





Website: www.remee.com



Issue Date: 01/2020 Revision: 7

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Fax: 845-651-4160

Page 1 of 3



Category 6 Shielded 550MHz Plenum

ETL verified for guaranteed performance

Made in the USA

Part No.: 6B234STPENH

Electrical Characteristics:

Frequency	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	20.0	2.0	80.3	78.3	73.8	70.8	78.3	76.3
4	23.0	3.8	71.3	69.3	61.8	58.8	67.5	65.5
10	25.0	6.0	65.3	63.3	53.8	50.8	59.3	57.3
16	25.0	7.6	62.2	60.2	49.7	46.7	54.6	52.6
20	25.0	8.5	60.8	58.8	47.8	44.8	52.3	50.3
31.25	23.6	10.7	57.9	55.9	43.9	40.9	47.2	45.2
62.5	21.5	15.4	53.4	51.4	37.9	34.9	38.0	36.0
100	20.1	19.8	50.3	48.3	33.8	30.8	30.5	28.5
200	18.0	29.0	45.8	43.8	27.8	24.8	16.8	14.9
250	17.3	32.8	44.3	42.3	25.8	22.8	11.5	9.5
300	16.8	36.4	43.1	41.1	24.3	21.3		
350	16.3	39.8	42.1	40.1	22.9	19.9		
400	15.9	43.0	41.3	39.3	21.8	18.8		
500	14.8	49.5	40.2	38.2	20.0	17.0		
550	14.4	53.1	39.5	37.5	18.9	15.9		

^{*}Values above 250 MHz are for engineering information only

Preparation For Shipment

Customer Service: 800-431-3864

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Website: www.remee.com



Issue Date: 01/2020 Revision: 7

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Fax: 845-651-4160

Page 2 of 3



Category 6 Shielded 550MHz Plenum

ETL verified for guaranteed performance

Made in the USA

Part No.: 6B234STPENH

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Wire & Cable warranty is an integral part of this specification. This item may be non-cancelable and non-returnable.
Signature:
Company:
Date:

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order. The Remee





Website: www.remee.com



Issue Date: 01/2020 Revision: 7

Customer Service: 800-431-3864

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Fax: 845-651-4160