

Part No.: 725102

Applications

This document establishes the specifications for an RG-59/U, 75 ohms, plenum coaxial cable used for CCTV or closed circuit camera systems, computer broadcast and communication applications.

Construction Details

Center Conductor: 20AWG Solid bare copper Dielectric Material: Foamed FEP (Teflon) Nominal Dielectric Core O.D: 0.135 in. 1st shield: CCA Braid Jacket Material: Remguard Plenum Polymer Nominal Overall Diameter: 0.202 in. Jacket Color: Per Customer Requirement Surface Print: 3122598 CMP RG59/U 20AWG C(ETL)US FT6 + Sequential Footage Marking


Electricals

Nominal Capacitance: 17.3 pF/ft. Nominal Characteristic impedance: 75 Ω Nominal Velocity of propagation: 78% Nominal attenuation per 100 ft.:

2.8 dB @ 100 MHz 4.1 dB @ 200 MHz 6.3 dB @ 400 MHz 9.2 dB @ 700 MHz

RG59 Coaxial Cable Plenum

ETL listed for guaranteed performance Made in the USA



Technical Details

Temperature Rating

	Operation:	-2°C to +60°C
Nominal Weight:		24 lbs. / 1,000 ft.

Standards

- NEC Article 800
- CMP Rating FT6

Codes & Listings

C(ETL)US

Preparation For Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 06/15 Revision: 4

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com



RG59 Coaxial Cable Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: 725102

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

agreed to this :	e constitutes that you have read and specification sheet and upon confirma- der; this item may be non-cancelable nable.
Signature:	
Company:	
Date:	



Issue Date: 06/15 Revision: 4

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com