

12-2 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725120

Applications:


This document establishes the specifications for a plenum-rated two conductor unshielded cable used for communications and signaling power limited circuit applications.

Construction Details:

Number of Conductors: 2/C
Conductor: 12AWG Stranded Bare Copper
Insulation Material: Remguard Plenum Polymer
Nominal Insulation Thickness: 0.009 in.
Nominal Insulation Diameter: 0.107 in.
Color Code: Black, Red
Shield: N/A
Drain: N/A
Jacket Material: Remguard Plenum Polymer
Jacket Color: Per Customer Requirement
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.244 in.
Surface Print: VIGILANCE™ by REMEE CMP/
FPLP 12AWG C(ETL)US FT6 MADE IN USA
RoHS +Sequential Footage Marking

Electricals:

Suggested Working Voltage: 300 Volts, rms.
Nom. Impedance: 44 Ohms
DCR, Max. : 1.621 Ω / 1000' @ 20°C
Nom. Capacitance: 55 pF/Ft.
Nom. Velocity of Propagation: 55%



* Drawing Not To Scale

Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 52 lbs. / 1,000 feet

Standards:

- NEC Articles 800, 760
- UL Subject 1424, Type FPLP
- UL Subject 444, Type CMP FT6

Codes & Listings:

- C(ETL)US CMP



MADE IN THE USA




Issue Date: 04/22
Revision: 12

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



12-2 Unshielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725120

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — **M for 1000 feet**, and **L for 500 feet**

Available Put-Up's — **1 for Reel**, and **2 for Box**

Available Jacket Color — **W for White**, (Other Colors Available with Minimum Order Quantities)

These 3-place designators are placed at the end of the specific part number to fully describe the individual packaging and length.

Note: While Remeo Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeo Products Corp. does not guarantee that it is error-free, nor does Remeo Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeo Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeo Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____



MADE IN THE USA



Issue Date: 04/22
Revision: 12

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com