

18-8 Shielded Plenum

ETL listed for guaranteed performance
Made in the USA


Part No.: 725189

Applications:

This document establishes the specifications for an eight conductor plenum-rated shielded cable used for remote control and signaling power limited circuit applications.

Construction Details:

Number of Conductors: 8/C
 Conductor: 18AWG Stranded Bare Copper
 Insulation Material: Remguard Plenum Polymer
 Nominal Insulation Thickness: 0.007 in.
 Nominal Insulation Diameter: 0.060 in.
 Color Code: Black, Red, White, Green, Brown, Blue, Orange, Yellow
 Shield: Aluminum/Polyester Tape (100% Coverage)
 Drain: Solid Tinned Copper
 Jacket Material: Remguard Plenum Polymer
 Nominal Jacket Thickness: 0.015 in.
 Nominal Diameter: 0.232 in.
 Surface Print: VIGILANCE™ by REMEE CMP/FPLP
 8AWG C(ETL)US FT6 MADE IN USA
 + Sequential Footage marking



Technical Details:

Temperature Rating

Operation: -2°C to +60°C

Nominal Weight: 60 lbs. / 1,000 ft.

Standards:

- NEC Articles 800, 760
- UL Subject 1424, Type FPLP
- UL Subject 444, Type CMP FT6

Electricals:

Suggested Working Voltage: 300 Volts, rms.
 Nom. Capacitance Cond-Cond: 76 pF/ft
 Nom. Capacitance Cond-Shield: 142 pF/ft
 Nom. Impedance: 6 Ohms/1M'
 Nom. Velocity of Propagation: 55%

Codes & Listings:

- C(ETL)US CMP




Issue Date: 04/22
Revision: 9

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



18-8 Shielded Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: 725189

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — **M for 1000 feet**, and **L for 500 feet**

Available Put-Up's — **1 for Reel**, and **2 for Box**

Available Jacket Color — **W for White**, (**Other Colors Available with Minimum Order Quantities**)

These 3-place designators are placed at the end of the specific part number to fully describe the individual packaging and length.

Note: While Remeo Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeo Products Corp. does not guarantee that it is error-free, nor does Remeo Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeo Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeo Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____
Company: _____
Date: _____



Issue Date: 04/22
Revision: 9

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com