

Part No.: CH1000F

Applications:

This document establishes the specifications for a two conductor cable used in audio and power limited circuit applications.

Construction Details:

Number of Conductors: 2/C

Conductor: 14 AWG 105/34 Bare Copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.012 in. Nominal Insulation Diameter: 0.097 in.

Color Code: Black, Red

Jacket Material: Polyvinyl Chloride Nominal Jacket Thickness: 0.018 in.

Nominal Diameter: 0.230 in.

Surface Print: 3122598 HI-STRAND AUDIO

CABLE CSA C(ETL) FT4 2 COND 14AWG 105 STRAND 75°C CL3R (ETL)US MADE IN USA...SUITABLE FOR OUTDOOR USE...OXYGEN FREE COPPER + Sequential

Footage Marking

Electricals:

Working Voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Issue Date: 11/16

Revision: 6


Operation -20°C to +75°C

Nominal Weight: 38 lbs. / 1,000 Feet

14-2 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance

Made in the USA



Standards:

- NEC Article 725
- UL Subject 13, Type CL3R FT4

Codes & Listings:

- (ETL)US
- C(ETL)

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.







All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

1



14-2 Unshielded Audio Cable Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: CH1000F

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	on sheet and upon confirmation of your or- nay be non-cancelable and non-returnable.
Signature:	
Company:	
_	
Date: —	







Issue Date: 11/16 Revision: 6 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com