

22-2 Shielded 18-1 Unshielded 12-2 Unshielded Plenum

Part No.: LUGRX46LP

Applications:

This document establishes the specifications for a composite cable used for power limited applications.


Construction Details:

Number of Conductors: 2/C (1 pair)
 Conductor: 22AWG Stranded Bare Copper
 Insulation Material: FEP
 Nominal Insulation Thickness: 0.012 in.
 Nominal Insulation Diameter: 0.053 in.
 Color Code: White paired with Green
 Tape: Polyester
 Shield: Aluminum/Polyester Tape (100% Coverage)
 Drain: Tin Copper

Number of Conductors: 1/C
 Conductor: 18AWG Stranded Bare Copper
 Insulation Material: Remguard
 Nominal Insulation Thickness: 0.008 in.
 Nominal Insulation Diameter: 0.062 in.
 Color Code: Orange

Number of Conductors: 2/C
 Conductor: 12AWG Stranded Bare Copper
 Insulation Material: Remguard
 Nominal Insulation Thickness: 0.009 in.
 Nominal Insulation Diameter: 0.118 in.
 Color Code: Red, Black

Jacket Material: Remguard
 Jacket Color: White With Blue Stripe
 Nominal Diameter: 0.325 in.
 Surface Print: PLENUM LUTRON GRX-PCBL-46L
 TYPE - 3122598 12AWG 2C + 18AWG 1C + 22AWG
 1PR SHIELDED DATA 75°C (ETL)US CL3P ROHS
 MADE IN USA + Sequential Footage Marking



Electricals:

Suggested Working Voltage: 150 V RMS
 Capacitance Cond-Cond 22AWG: 25 pF/FT
 Impedance: 61 Ω
 DCR 22awg: 15.0 Ω/1M'
 DCR 18awg: 6.53 Ω/1M'
 DCR 12awg: 1.73 Ω/1M'

Technical Details:

Temperature Rating	Operation	-2°C to +75°C
Nominal Weight:	72 Lbs. / 1,000 ft.	

Standards:

- National Electric Code - Article 725
- UL Subject 13

Codes & Listings:

- (ETL)US CL3P




Issue Date: 5/20
 Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



22-2 Shielded
18-1 Unshielded
12-2 Unshielded
Plenum

Part No.: LUGRX46LP

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Note: While Remeë Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeë Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeë Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order. The Remeë Wire & Cable warranty is an integral part of this specification. This item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____



Issue Date: 5/20
Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com