

# 22-2 Shielded 12-2 Unshielded Plenum

## Part No.: LUQSHLPM1WN

### **Applications:**

This document establishes the specifications for a two pair, one pair shielded cable used for communication applications.

#### **Construction Details:**

Conductor: 22AWG Stranded Bare Copper.

Insulation Material: FEP

Nominal Insulation Thickness: 0.012 in. Nominal Insulation diameter: 0.053 in. Color Code: White paired with Blue

Shield: Aluminum/Polyester Tape (100% Coverage)

Drain: 24AWG 7/32 Tin Copper

Conductor: 12AWG Stranded Bare Copper.

Insulation Material: Remguard

Nominal Insulation Thickness: 0.012 in. Nominal Insulation Diameter: 0.117 in.

Color Code: Black, Red

Jacket Material: Remguard

Jacket Color: White with a Brown Stripe

Nominal Diameter: 0.310 in.

Surface Print: 3122598 2/C 12 + 2/C 22 SHIELDED

(ETL)US CL3P MADE IN USA + Sequential Footage Marking

#### **Electricals:**

Suggested Working Voltage: 300 V RMS Max. Capacitance Cond-Cond: 25 pF/FT

#### **Technical Details:**

**Temperature Rating** 

Operation -2°C to +75°C

Nominal Weight: 68 Lbs. / 1,000 ft.

#### Standards:

- National Electric Code Article 800
- UL Subject 13 Type CL3P

### **Codes & Listings:**

(ETL)US FT6

## **Preparation for Shipment:**

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/18 Revision: 2

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



# 22-2 Shielded 12-2 Unshielded Plenum

Part No.: LUQSHLPM1WN

**Note:** While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Data:	

Your signature constitutes that you have read and agreed to



Issue Date: 06/18 Revision: 2

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com