


14-2 Shielded Local Law #39 Fire Alarm

ETL listed for guaranteed performance Made in the USA



Part No.: NY514ST

Applications:

This document establishes the specifications for a two conductor shielded cable used for Local Law #39 fire alarm installations.

Construction Details:

Number of Conductors: 2/C twisted Conductor: 14AWG Solid Bare Copper.

Insulation Material: FEP

Nominal Insulation Thickness: 0.016" Nominal Insulation Diameter: 0.096"

Color Code: Black. Red

Shield: Aluminum/Polyester Tape (100% Coverage)

Drain: Tin Copper Jacket Material: FEP Jacket Color: Red

Nominal Jacket Thickness: 0.026"

Nominal Diameter: 0.248"

Surface Print: VIGILANCE™ by REMEE TYPE FPLP 14AWG SHIELDED 200°C (ETL)US ALSO CLASSIFIED NYC CERT. FIRE ALARM CABLE LL39 MADE IN USA + SEQUENTIAL FOOTAGE

MARKING

Electricals:

Suggested Working Voltage: 300 Volts, rms. Nominal Capacitance Cond-Cond: 50 pF/ft.

DCR, Min.: 2.575 Ω/1000'@20°C

Insulation Resistance:>100 Megohms/1M' @ 60°C

Velocity of Propagation: 69%

Impedance: 29 Ω

Technical Details:

Temperature Rating

Operation -20°C to 200°C

Nominal Weight 59 lbs. / 1,000 ft.

Standards:

- National Electric Code—Article 760 Type FPLP
- Building Code City of New York
- Certified For Use In New York City, Local Law No. 39
- NFPA 262

Codes & Listings:

- UL Subject 1424
- (ETL)US FPLP

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





Issue Date: 12/21 Revision: 5

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



14-2 Shielded Local Law #39 Fire Alarm

ETL listed for guaranteed performance Made in the USA

Part No.: NY514ST

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — M for 1000 feet, and L for 500 feet Available Put-Up's — 1 for Reel, and 2 for Box Available Jacket Color — R for Red

These 3-place designators are placed at the end of the specific part number for LL39 compliant parts to fully describe the individual packaging and length.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	onstitutes that you have read and agreed to a sheet and upon confirmation of your order; non-cancelable and non-returnable.
Signature:	
Company:	
Date:	





Issue Date: 12/21 Revision: 5

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com