


Part No: REMEX11-XX-XXX-XIALA

Issue Date: 08/30/2018

Revision #: 00

REMEX11-Series Interlock Armor I/O Tight Buffer Distribution Fiber Optic Cable

Cable Cross Section



(Representation of a standard 12 fiber construction)

Scope

This document establishes the specification requirements for a indoor/outdoor armor distribution fiber optic cable. This cable construction consists of a distribution tight-buffer design with an interlocking armor and a plenum rated

Applications

Outdoor direct burial, Aerial Lashed, Indoors in the riser space and Tray Installations

Applicable Documents

- TIA/EIA FOTP Standards 455
- Color Coding of Fiber Optic Cables TIA/EIA-598
- UL 1666
- GR-409 CORE
- Compliant with ANSI/TIA-568-C.3 standard

Cable Construction Details

- Tight Buffered Fiber
Dimension: 900µm, Nominal
- Tight Buffer Color Code:
As per TIA/EIA-598 standard or per customer requirement
- Cable Strength:
Water swellable aramid yarns are pulled in with tight-buffered fibers under the inner sheath.
- Inner Sheath: UV Resistant Riser Rated Polyvinyl Chloride
- Armor: Aluminum Interlocking Armor
- Overall Sheath: UV Resistant Riser Rated Polyvinyl Chloride

Continued

Nominal Cable Dimensions & Weights			
Remeë Products Part Number	Number of Fibers	Cable OD in (mm)	Weight lb/1000ft (kg/km)
REMEX11002XXXXIALA	2	0.605(15.4)	125 (186)
REMEX11004XXXXIALA	4	0.605(15.4)	127 (189)
REMEX11006XXXXIALA	6	0.605(15.4)	130 (193)
REMEX11008XXXXIALA	8	0.605(15.4)	132 (196)
REMEX11012XXXXIALA	12	0.655(16.6)	152 (226)
REMEX11024XXXXIALA-T	24	0.638 (16.2)	135 (201)

**Cables printed in meters will have a "-MR" suffix on the part number.*

Jacket Color	
Designation	Color
B	Black
Y	Yellow
Z	Orange
A	Aqua
M	Violet

Fiber Type (P/N)	Maximum Attenuation dB/km				Overfill Launch Min Bandwidth (MHz-km)		EMBe (MHz-km)	Gigabit Ethernet Minimum Link Distance (Meters)		10 Gigabit Ethernet Minimum Link Distance (Meters)	
	850 nm	1300 nm	1310 nm	1550 nm	850 nm	1300 nm		850 nm	1300 nm	850 nm	1300 nm
62.5µm OM1 1GIG (22J)	3.2	1.0	N/A	N/A	200	600	N/A	300	550	32	-
50µm OM2 10GIG (12D)	3.0	1.0	N/A	N/A	750	500	N/A	800	550	150	-
50µm OM3 10GIG (12N)	3.0	1.0	N/A	N/A	1500	500	2000	1000	550	300	-
50µm OM4 10GIG (12V)	3.0	1.0	N/A	N/A	3500	500	4700	1040	550	550	-
SM OS2 G.652.D (76K)	N/A	N/A	0.40	0.30	N/A	N/A	N/A	N/A	5000	N/A	10000
SM OS2 G.652.D (74K)	N/A	N/A	0.35	0.25	N/A	N/A	N/A	N/A	5000	N/A	10000
SM OS2 G.652.D/G.657.A1 BIF (76U)*	N/A	N/A	0.40	0.30	N/A	N/A	N/A	N/A	5000	N/A	10000
SM OS2 G.652.D/G.657.A2, B2 BIF (76F)**	N/A	N/A	0.40	0.30	N/A	N/A	N/A	N/A	5000	N/A	10000

** G.657.A1 (76U) Mandrel Radius of 10mm, 1 turn at 1550nm with an induced attenuation of ≤0.50dB*

*** G.657.A2,B2 (76F) Mandrel Radius of 7.5mm, 1 turn at 1550nm with an induced attenuation of ≤0.40dB*

Please call the factory for all other fiber types

Continued



Mechanical & Environmental Performance

Cable Without Armor

- Maximum Tensile Load

Installation : 2&4 fiber 1405N / 315lbf
6&8 fiber 1610N / 362lbf
12&24 fiber 2700N / 600lbf

Long Term : 2&4 fiber 455N / 102lbf

6&8 fiber 535N / 120lbf
12&24 fiber 600N / 135lbf

- Crush Resistance

100 N/cm

- Impact Resistance (min.)

25 Impacts

- Flexing $\pm 90^\circ$ (min.)

25 Cycles

- Temperature Rating

Operation : -40°C to +85°C
Installation : 0°C to +75°C
Storage : -55°C to +85°C

Cable With Armor

- Maximum Tensile Load

600N / 150lbf

- Crush Resistance

1000 N/cm

Warranty Information

All warranty information can be viewed at www.remee.com. This product is RoHS compliant and is directive 2002/95/EC. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice.

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Note: While Remeo Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remeo Products Corp. does not guarantee that it is error-free, nor does Remeo Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remeo Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remeo Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this documents are for reference purposes only and are subject to change without notice.

Spec Approval (Custom Designs Only)

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order: this item may be non-cancelable and non-returnable.

Signature: _____ Date: _____