

Category 5e + 18/2 Siamese Plenum

ETL listed for guaranteed performance

Made in the USA

Part No.: RMMS5BE725181

Applications:

This document establishes the specifications for a cable containing one Category 5e and a two conductor 18AWG shielded cable in a siamese construction with a low smoke jacket.

2c18 Construction Details:

Conductor: 18AWG Stranded Bare Copper

Number of Conductors: 2/C Insulation Material: Low Smoke PVC Insulation Color: Black, Red Drain Wire: Stranded Tin Copper

Shield: Aluminum/Polyester (100% coverage)

Cat5e Construction Details:

Conductor: 24AWG Solid Bare Copper. Number of Conductors: 4 Pairs (8/C)

Insulation Material: FEP.

Overall Cable Construction Details:

Construction Type: One Cat5e and one 2c18AWG shielded

are pulled in parallel at extrusion in a

siamese construction.

Jacket Material: Low Smoke PVC

Jacket Color: Per Customer Requirement Nominal Jacket Thickness: 0.018 in.

Nominal Overall Diameter: Minor over Cat5e: 0..206 in.

Minor over 2c18: 0.170 in.

Major: 0.401 in. Surface Print: ETL VERIFIED CAT5E TO

TIA-568C.2...3122598 CMP 24AWG 4UTP

CAT5E 2/C 18AWG SHIELDED

C(ETL)US FT6 MADE IN USA + Sequential

Footage Markings

Standards:

- NEC Article 800
- UL Standard 444
- ANSI/TIA/EIA 568C.2 Category 5e

Codes & Listings:

- CMP Rating
- C(ETL)US

Electrical Parameters (Cat5e):

Nominal Mutual Capacitance: 14 pF/ft

Maximum Capacitance Unbalance: 330 pF/ft

Velocity of Propagation: 72%

Max. Conductor D.C.R.: 28.6 ohm/1000 feet

Max. DCR Unbalance: 5%

Max. Delay Skew: 45.0 ns/100m

Characteristic Impedance: from 0.772 - 100 MHz 100 ± 15%





All warranty information can be viewed at

Issue Date: 07/17

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



Category 5e + 18/2 Siamese Plenum

ETL listed for guaranteed performance Made in the USA

Part No.: RMMS5BE725181

Electrical Characteristics:

Frequency	SRL	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
	dB	dB	dB(100m)	dB	dB	dB	dB	dB	dB
MHz	Minimum	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	23.0	20.0	2.0	65.3	62.3	63.8	60.8	63.3	60.3
4	23.0	20.3	4.0	56.3	53.3	51.7	48.7	52.3	49.3
8	23.0	20.5	5.7	51.8	48.8	45.7	42.7	46.1	43.1
10	23.0	25.0	6.4	50.3	47.3	43.8	40.8	43.9	40.4
16	23.0	25.0	8.2	47.3	44.3	39.7	36.7	39.1	36.1
20	23.0	25.0	9.2	45.8	42.8	37.7	34.7	36.6	33.6
25	22.0	25.0	10.4	44.3	41.3	35.8	32.8	33.9	30.9
31.25	21.1	23.6	11.7	42.9	39.9	33.9	30.9	31.2	28.2
62.5	18.1	21.5	16.9	38.4	35.4	27.8	24.8	21.5	18.5
100	16.0	20.1	21.9	35.3	32.3	23.8	20.8	13.4	10.4

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.





All warranty information can be viewed at WWW.REMEE.COM.

Issue Date: 07/17 Revision: 0

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



Category 5e + 18/2 Siamese Plenum

ETL listed for guaranteed performance
Made in the USA

Part No.: RMMS5BE725181

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	n sheet and upon confirmation of your or- ay be non-cancelable and non-returnable.
Signature:	
Company:	
Date:	





All warranty information can be viewed at WWW.REMEE.COM.

Issue Date: 07/17 Revision: 0

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921 Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com

Page 3 of 3