

Hybrid SMPTE 311M HDTV 3-Channel Indoor CMR/Outdoor (Wet Location) Riser Rated

Spec Part No.: 3CSMPTRW

Construction Details - Component 1

Conductor: 18AWG 19/30 TC Insulation: Polyethylene

Nominal Diameter:

Colors: Black, White, Blk/Yel, Wht/Yel, Blk/Orn, Wht/Orn

0.078 in.

Construction Details - Component 2

Conductor: 24AWG 7/32 TC
Insulation: Polyethylene
Nominal Diameter: 0.044 in.

Colors: Red, Gray, Red/Yel, Gry/Yel, Red/Orn, Gry/Orn

Construction Details - Component 3

Fiber Type: BIF Singlemode G.657A1

Buffer: Tight Buffer 900 ± 50 micron (.035 \pm .002 in.)

Strength Member: Water swellable aramid yarns

Sub Unit OD: $0.114 \pm .005$ in. Sub Unit Material: Polyvinyl Chloride

Color Code: Yellow numbered 1—6.

Overall Construction Details

Filler: Solid PVC. Fibrillated Polypropylene for roundness.

Cable Assembly: Two 18awg and two 24awg cabled with drain wire and

shield. Three components and six fiber cabled in 8.00in

left hand lay.

Tape: Water Block Tape

Jacket Material: PVC

Jacket Thickness: 0.050in., Nominal

Nominal Diameter: 0.621 in.


Jacket Color: UV Resistant Black, (Other Colors Available with MOQ)

Surface Print: ClearCast™ by REMEE THREE-CHANNEL HYBRID

FIBER CAMERA CABLE CMR C(ETL)US FT4 75°C ROHS ...SUITABLE FOR WET LOCATION... MADE IN

USA MM/YY (LOT #) SEQ FT

Footage Marking: Sequentially Marked every 2 Ft.



Electricals

Voltage Rating: 300V Optical Attenuation @ 1310nm: \leq 0.5 dB/km Optical Attenuation @ 1550nm: \leq 0.5 dB/km Component 1 (18AWG) DCR: 6.21 Ω /1M' @ 20°C

26.25 Ω/1M' @ 20°C

Technical Details

Component 2 (24AWG) DCR:

Temperature Rating

Operation -20°C to +75°C
Installation: 0°C to +60°C

Nominal Weight/1M' 212 lbs

Maximum Cable Pull Strength 95 lbs

Minimum Bend Radius 4.3 in.

Codes & Listings

• UL 1666: CMR rating FT4

C(ETL)US CMR

SMPTE 311

UL Subject 444

Product Part Number

1202SMPTE3CHRWBT





Issue Date: 01/25

Revision: 7

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



Hybrid SMPTE 311M HDTV 3-Channel Indoor CMR/Outdoor (Wet Location) Riser Rated

Spec Part No.: 3CSMPTRW

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length's and Put-Up's — M1 for 1,000' reel; B2 for 2,000' reel; B3 for 2,500' reel; B5 for 5,000' reel Available Jacket Color — B for Black, (Other Colors Available with Minimum Order Quantities)

The 3-place designator is placed at the end of the part number to describe specific packaging, length and jacket color.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	





Issue Date: 01/25 Revision: 7

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.