

24-1P Shielded Digital Audio Riser

ETL listed for guaranteed performance
Made in the USA

Spec Part No.: AUD1P24SR

Applications:


This document establishes the specifications of a two conductor riser-rated shielded cable used for communication applications.

Construction Details:

Number of Conductors: 2/C
Conductor: 24AWG 7 Strand Tin Copper
Insulation Material: Polyethylene Foam
Nominal Insulation Thickness: 0.025 in.
Nominal Insulation Diameter: 0.074 in.
Color Code: Black, Red
Drain: 24AWG 7 Strand Tin Copper
Shielding: Aluminum/Polyester Tape (100% coverage)
Jacket Material: Polyvinyl Chloride
Jacket Color: Gray (Others with MOQ)
Nominal Jacket thickness: 0.020 in.
Nominal Diameter: 0.191 in.
Surface Print: ClearCast™ by REMEE 24AWG 1P
C(ETL)US CMR FT4 MM/YY (LOT #) MADE IN
USA SEQ FT

Electricals:

Suggested Working Voltage: 300 Volts, rms.
Conductor DCR, Nom.: 26.1 Ohms/1000 ft
Capacitance, Cond to Cond, Nom.: 11 pF/ft
Capacitance, Cond to Others, Nom.: 25 pF/ft
Nom. Characteristic Impedance: 110 Ohms
Nom. Velocity of Propagation: 75%
Max. Current per Cond @ 30°C: 3.8 Amps



Technical Details:

Temperature Rating

Installation: 0°C to + 50°C

Operation: -30°C to + 60°C

Nominal Weight: 16 lbs. / 1,000 ft.

Max Installing Tension: 11 lbf

Min Bending Radius: 1.9 in

Standards:

- National Electric Code - Article 800
- UL Subject 444
- CMR Type FT4

Codes & Listings:

- C(ETL)US CMR
- C(ETL) FT4

Product Part Number

N/A



MADE IN THE USA




Issue Date: 07/25
Revision: 8

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



24-1P Shielded Digital Audio Riser

ETL listed for guaranteed performance
Made in the USA

Spec Part No.: AUD1P24SR

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — **M** for 1000 feet, and **L** for 500 feet

Available Put-Up's — **1** for Reel, and **2** for Box

Available Jacket Color — **G** for Gray, (Other Colors Available with Minimum Order Quantities)

These 3-place designators are placed at the end of the specific part number to fully describe the individual packaging and length.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____



MADE IN THE USA



Issue Date: 07/25
Revision: 8

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com