




16-2 Unshielded Speaker Cable Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Spec Part No.: SPK2C16R

Applications:


This document establishes the specifications for a riser-rated two conductor unshielded cable used for speaker cable applications.

Construction Details:

Number of Conductors: 2/C
Conductor: 16AWG 19/29 OFC Bare Copper
Insulation Material: Polyvinyl Chloride
Nominal Insulation Thickness: 0.009 in.
Nominal Insulation Diameter: 0.075 in.
Color Code: Black, Red
Cable Lay: 5.0 in. Left Hand Lay
Jacket Material: Polyvinyl Chloride
Jacket Color: White or Black; (Others Available with Minimum Order Quantity)
Nominal Jacket Thickness: 0.015 in.
Nominal Diameter: 0.180 in.
Surface Print: ClearCast™ by REMEE 16AWG 2C 75C C(ETL)US CMR FT4 RoHS MM/YY (LOT #)
MADE IN USA SEQ FT

Electricals:

Suggested Working Voltage: 300 Volts, rms.
Conductor DCR, Nom.: 4.2 Ω/1000 ft
Capacitance, Cond to Cond, Nom.: 49 pF/ft
Impedance, Nom.: 46 Ω
Max. Current per Cond @ 25°C: 6.25 Amps
Velocity of Propagation: 45%



Technical Details:

Temperature Rating

Installation: 0°C to + 50°C

Operation: -20°C to + 75°C

Nominal Weight: 23 lbs. / 1,000 ft.

Max Installing Tension: 39 lbf

Min Bending Radius: 1.8 in

Standards:

- National Electric Code - Article 725
- UL Subject 444
- CMR Type FT4

Codes & Listings:

- C(ETL)US CMR
- C(ETL) FT4

Product Part Number

2C16VV/19BCW




Issue Date: 06/25
Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



16-2 Unshielded Speaker Cable Non-Plenum

ETL listed for guaranteed performance
Made in the USA

Spec Part No.: SPK2C16R

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length Designations — **M** for 1000 Feet; **L** for 500 Feet; **J** for 300 Meters (984'); **H** for 150 Meters (492')

Available Put-Up's — **1** for Reel, and **2** for Box

Available Jacket Color — **W** for White, **B** for Black, (Other Colors Available with Minimum Order Quantities)

These 3-place designators are placed at the end of the specific part number to fully describe the individual packaging and length.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____



MADE IN THE USA



Issue Date: 06/25
Revision: 0

All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921
Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com