

Spec Part No.: SPK2C12SP

Applications:

This document establishes the specifications for a plenum rated two conductor shielded cable used in speaker cable applications.

Construction Details:

Number of Conductors: 2/C
Conductor: 12AWG 65/30 Bare Copper
Insulation Material: Remguard Plenum Polymer
Insulation Thickness: 0.015 in.
Nominal Insulation Diameter: 0.123 in.
Color Code: Black, Red
Shield: Aluminum/Polyester Tape (100% Coverage)

Aluminum Side Out

Drain: 20AWG Stranded Tin Copper Drain Jacket Material: Remguard Plenum Polymer Jacket Color: White or Black (Others Available with

Minimum Order Quantity)

Jacket Thickness: 0.015 in.

Nominal Diameter: 0.279 in.

Rip Cord: Nylon

Surface Print: ClearCast™ by REMEE 12AWG 2C

75C C(ETL)US CL3P FT6 RoHS MM/YY

(LOT #) MADE IN USA SEQ FT

Electricals:

Suggested Working Voltage: 300 Volts, rms. Conductor DCR, Nom.: 1.52 Ohms/1000 ft

Capacitance, Cond to Cond, Nom.: 97.0 pF/ft

Capacitance, Cond to Others, Nom.: 175.6 pF/ft


Impedance, Nom.: 25 Ohms

Max. Current per Cond @ 25°C: 26 Amps

Velocity of Propagation: 42%

12-2 Shielded Speaker Cable Plenum

ETL listed for guaranteed performance
Made in the USA



Technical Details:

Temperature Rating

Installation: 0°C to + 50°C

Operation: -20°C to + 75°C

Nominal Weight: 66 lbs. / 1,000 ft.

Max Installing Tension: 113 lbf

Min Bending Radius: 2.8 in

Standards:

- National Electric Code Articles 800, 760
- UL Subject 1424, Type FPLP
- UL Subject 444, Type CMP FT6

Codes & Listings:

- (ETL)US CL3P
- C(ETL) FT6







Issue Date: 08/25 Revision: 4 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com



12-2 Shielded Speaker Cable Plenum

ETL listed for guaranteed performance
Made in the USA

Spec Part No.: SPK2C12SP

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

Specific Part Number Information for Length, Put-Up & Jacket Color:

Available Length's and Put-Up's — M1 for 1,000' reel; B2 for 2,000' reel; B3 for 2,500' reel; B5 for 5,000' reel

Available Stock Jacket Color — W for White, B for Black (Other Colors Available with Minimum Order Quantities)

The 3-place designator is placed at the end of the part number to describe specific packaging, length and jacket color.

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	







Issue Date: 08/25 Revision: 4 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

1751 State RTE. 17A STE #1 Florida, NY 10921

Customer Service: 800-431-3864 Fax: 845-651-4160 Website: www.remee.com